



SRL-26S



CARACTÉRISTIQUES

- ✓ Enceinte d'ambiance large bande
- ✓ HP grave/medium 2 x 6" avec moteur d'aigu de 1"
- ✓ Montage aisé par une seule personne
- ✓ Fixation mur ou plafond

Répondant aux besoins des salles de moyenne taille, la **SRL-26S** est une enceinte d'ambiance 2 voies offrant une restitution étendue dans les basses et un haut rendement.

Cette version paysage ou horizontale permet son utilisation en plafond, en sous cabine ou dans des configurations exigeuses.

Comme toutes les enceintes de la série **Studio**, cette solution haute performance offre une reproduction sonore puissante, détaillée et naturelle.

SPÉCIFICATIONS

Bande passante (-10dB) ¹	56 Hz - 18 kHz
Puissance AES admissible ²	400 W
Puissance programme ³	520 W
Sensibilité (1w/1m) ⁴	93 dB SPL
SPL maximum (1m)	119 dB
Impédance nominale	4 Ω
Directivité horizontale (-6dB)	90°
Directivité verticale (-6dB)	60°
Dimensions (HxLxP) SRL-10C	300 mm x 750 mm x 300 mm
Poids net	13 kg

(1) Free field, -10dB from on-axis sensitivity

(2) AES continuous pink noise, 2 hours duration

(3) Continuous program power is defined as 3 dB greater than AES continuous pink noise and is a conservative expression of the transducer's ability to handle normal music program material

(4) 1W / 1m, Average measured free field, 2.83V

Les informations et photos sont non contractuelles et sujettes à modification sans préavis.



SCHÉMAS TECHNIQUES SRL-26S

